

AU-VC200H



Description

- B/W dome
- 1/3" SONY Super HAD CCD
- 420 TV lines

Specification

| Item | AU-VC-200H (B/W) | | | |
|------------------------|---|---|---|---|
| Pickup Device: | 1/3" LG CCD | 1/4" SONY Super HAD CCD | 1/3" SONY Super HAD CCD | |
| Picture Elements: | CCIR: 500(H) x 582(V) EIA: 510(H) x 492(V) | PAL: 500(H) x 582(V) NTSC: 510(H) x 492(V) | CCIR: 500(H) x 582(V) EIA: 510(H) x 492(V) | PAL: 500(H) x 582(V) NTSC: 510(H) x 492(V) |
| Sensing Area: | 4.9 x 3.7mm | 3.6 x 2.7mm | 4.9 x 3.7mm | |
| System of Signal: | CCIR/EIA | PAL/NTSC | CCIR/EIA | PAL/NTSC |
| Horizontal Resolution: | 420TV Lines | | | |
| Lens Mount: | 3.6mm,6mm,8mm,12mm Selectable | | CS Mount-lens can be applied | |
| Electronic Shutter: | 1/50(1/60)-1/100.000 sec | | | |
| S/N Ration: | More than48dB | | | |
| Minimum Illuminator: | 0.1Lux/F1.2 | 1.0Lux/F1.2 | 0.05Lux/F1.2 | 0.8Lux/F1.2 |
| Video Output: | 1.0Vp-p,75 | | | |
| Power Requirement: | DC 12V | | | |
| Power Consumption: | 100mA | 120mA | 100mA | 120mA |
| Video Out | BNC | | | |
| Dimensions: | □ x 65mm | | □ x 110mm | |