

DS-2CE5AU1T-AVPIT3ZF 4K Vandal Motorized Varifocal Dome Camera



- 8 MP dome camera
- Lens focuses automatically when zooming in or out
- EXIR 2.0: advanced infrared technology with 60 m IR distance
- Water and dust resistant (IP67) and vandal proof (IK10)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

| Camera | |
|--------------------|---|
| Image Sensor | 8.29 megapixel progressive scan CMOS |
| Max. Resolution | 3840 (H) × 2160 (V) |
| Min. Illumination | Color: 0.01 Lux @ (F2.4, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/12.5 s to 1/50,000 s; NTSC: 1/15 s to 1/50,000 s |
| Day & Night | IR Cut Filter |
| Angle Adjustment | Pan: 0° to 355°, Tilt: 0° to 75°, Rotate: 0° to 355° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | 2.7 mm to 13.5 mm motorized vari-focal lens |
| Focal Length & FOV | 108.1° to 45.6° |
| Lens Mount | Φ14 |

| Illuminator | |
|--------------------------|---|
| Supplement Light Range | Up to 60 m |
| Image | |
| Image Settings | Brightness,Mirror,Smart IR,Sharpness |
| Frame Rate | TVI: 8MP@12.5fps, 8MP@15fps, 5MP@20fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps CVI: 8MP@12.5fps, 8MP@15fps AHD: 8M@12.5fps, 8M@15fps CVBS: 960H P/N |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| Wide Dynamic Range (WDR) | Digital WDR |
| Image Enhancement | BLC,HLC |
| Noise Reduction | 2D DNR |
| White Balance | Auto/Manual |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS,1 HD analog output |
| General | |
| Power | 9 VDC to 15 VDC -A: 9.6 VDC to 14.4 VDC; 19.2 VAC to 28.8 VAC *You are recommended to use one power adapter to supply the power for one camera. Max. 6.4 W -A: Max. 8.2 W |
| Material | Metal |
| Dimension | Ø 145 mm × 111.3 mm (Ø 5.69" × 4.37") |
| Weight | Approx. 860 g (1.90lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Communication | HIKVISION-C |
| Approval | |
| Protection | IP67 |

Signalumschaltung nur möglich bei 8MP.
Werkseinstellung 8MP TVI

