

WG-4kHD402FUV3

Art. 38813 4 Kanal 8MP All-Hybrid DVR



UNIVERSAL | Digital | Analog | IP | 4M QHD | 4K UHD | TDM RX

Key Features


- Digital : HD-SDI, EX-SDI(1.0, 2.x, 3.0), EX-SDI TDM 1.1
- Analog : AHD(8M), TVI(8M), CVBS(960H)
- IP(Ethernet) : Onvif, WESP
- Max. 4CH(2M, 4M), 2CH(4K UHD)
- Embedded TDM RX, 4K UHD(HDMI) output
- 2 Internal SATA HDDs
- External storage capacity 128TB(eSATA), 256TB(UHS04R)
- Real Time Streaming(RTSP)
- Service channel, Remote DVR
- VMS(Control Center), Mobile App(WebEye), HTML5 WebViewer

Dimension

(378×318×51mm)



<Front View>



<Rear View>

Tech Note

Universal & 4K UHD Support all kinds of existing video formats

From SD to UHD, including IPC, the Universal DVR support all kinds of video formats

The Universal DVR is the optimum solution for any site, any camera

DVR supports 4M QHD (2x greater than Full-HD) and 4KUHD (4x greater than Full-HD) recording

AI Camera Integration and Event Search

Remote settings of AI event, AI overlay, and object display through AI camera integration

Efficient event management and video monitoring through AI event filtering

Remote DVR Full control of remote DVR/NVR -Patent Application

Share DVR/NVR's main output on PC and real-time remote control from DVR/NVR's OSD menu on PC

Made in Korea

Competitive products having reliable quality and reasonable price purely developed and manufactured in Korea

Free VMS

Provide Central Monitoring Software (Control Center)for free, supporting Max. 1,024 DVRs with various and great functions.

WG-4kHD402FUV3



VIDEO INPUT		
Video input Format	BNC	HD-SDI, EX-SDI(1.0 / 2.x / 3.0), EX-SDI TDM 1.1, AHD, TVI, CVBS(960H,SD)
	IP(Ethernet)	WESP, Onvif Profile S H.264, H.265
Resolution / Frame Rate	HD-SDI	1920×1080@30fps, 1920x1080@25fps
	EX-SDI 1.0 EX-SDI 2.0	1920×1080@30fps, 1920x1080@25fps
	EX-SDI 2.1	2560×1440@30fps, 2560×1440@25fps 3840×2160@30fps, 3840×2160@25fps 3840×2160@15fps, 3840×2160@12fps
	EX-SDI 3.0	3840×2160@30fps, 3840×2160@25fps
	EX-SDI TDM 1.1	1920×1080@30fps, 1920x1080@25fps
	AHD	1920×1080@30fps, 1920x1080@25fps 2560×1440@30fps, 2560x1440@25fps 2560x1944@20fps, 2560x1944@20fps 3840×2160@15fps, 3840x2160@12fps
	TVI	1920×1080@30fps, 1920x1080@25fps 2560×1440@30fps, 2560x1440@25fps 2560x1944@20fps, 2560x1944@20fps 3840×2160@15fps, 3840x2160@12fps
	CVBS(960H)	960×480@60i, 720×480@60i 960×576@50i, 720×576@50i
	IP	1st stream: 704x576~3840x2160 2nd stream: 352x240~1280x720
Connectors		4ch, 75Ω BNC connector
CoC		Control over Coax@HD-SDI, EX-SDI1.0/2.x/3.0, AHD,TVI
VIDEO OUTPUT		
Video output	Resolution	HDMI : 3840×2160, 1920×1080 VGA : 1920×1080, 1280×1024, 1024×768 BNC(CVBS) : 720×480, 720×576
	Modes	HDMI main + VGA spot HDMI main + CVBS spot HDMI/VGA Duplicate HDMI/CVBS Duplicate HDMI main + VGA(Service Channel) HDMI main + CVBS(Service Channel)
	BNC(CVBS)	1, 4 split-screen, Switching
	BNC(SDI)	Not supported
RECORDING		
Compression	H.265 / H.264 / MJPEG	
Resolution	3840×2160, 2560x1944, 2560×1440, 1920×1080, 960×480	
Rate	Total 120fps, Max. 30fps/ch @1920×1080 Total 120fps, Max. 30fps/ch @2560×1440 Total 60fps, Max. 30fps/ch @3840×2160	
Quality	10 levels up to (Default - Q7) - H.264 : 4Mbps@2M, 6Mbps@4M, 6Mbps@5M, 8Mbps@8M(*) - H.265 : 3Mbps@2M, 4Mbps@4M, 4Mbps@5M, 6Mbps@8M(*)	
IP Camera	Same as BNC Camera	
Mode	Normal/Event Record, Schedule/Event Record, Emergency Record	
Schedule	24hrs / 7days	
PLAYBACK		
Mode	Instant Playback / Search	
Speed	Total 120fps, Max. 30fps/ch @1920×1080 Total 120fps, Max. 30fps/ch @2560×1440 Total 60fps, Max. 30fps/ch @3840×2160	
Search type	Date/Time, Calendar/Time-line, Event, Thumbnail(Interval/Motion), Text, Bookmark	
Block playback	1day ~ 365days	
EVENT & ALARM		
Event source	Motion detection, Sensor input, Video Loss, Text input, AI, Flame, Thermal, System	
Event check Schedule	24hrs / 7days	
Event action	Relay, Buzzer, E-mail, FTP, Video pop-up, Camera Preset, Mobile Alarm Push, System alarm	
MD area	15×10	
Text input	POS/ATM support, AVE VSI Pro/Hydra support	
SYSTEM ALARM		
Event source	HDD fail, HDD almost full, Password fail, WRS/DDNS fail, Recording Fail, NTP Sync Fail	
Event action	Pop-up Message, Buzzer, E-mail, Mobile Alarm Push	

AUDIO	
Input/output	4 RCA input / HDMI & RCA output
Compression	G.711
Direction	Both
PTZ	
Protocols	35 models including C1080, C1080PT-Z20, Pelco-D, Pelco-P, Samsung andPanasonic
NETWORK	
Interface	1 Fast Ethernet (10/100Mbps)
Type	Static IP, Dynamic IP, xDSL
DDNS	WNS, DynDNS, NoIP, WRS
Tx Bandwidth limit	1 ~ 77Mbps
NTP	Server / Client / Both
Users	Total 10 Users (Monitor + Playback) Playback 3 Users
RTSP	Supported
UPnP	UPnP auto port forwarding
Streaming	H.264 stream, H.265 stream High resolution 1 additional H.264 stream, H.265 stream Normal resolution 1 JPEG stream, Normal resolution
Service Streaming	Service Channel or Remote DVR
SECURITY	
User level	1 admin, 10 users
User privilege	Menu, PTZ, Playback, Power off, Copy, Network MIC, Camera setup
IP filtering	Supported
STORAGE & BACKUP	
Storage devices	2 internal SATA HDDs, 1 external eSATA Interface, Supported UHS04R
RAID Level	External storage including UHS04R (Level 1/5/10)
File system	High-performance proprietary file system Safe data protection in power interrupt Safe HDD head parking in power interrupt
Capacity	Max. 128TB with eSATA, Max. 256TB with cascaded UHS04R 12TB HDD Supported per SATA Port
Backup type	Multi-channel exe file, Single channel avi file, JPEG (Capture)
Backup device	2 USB 2.0 drive (1 front, 1 Rear) FAT32(Max 32GB), NTFS (Max 1TB)
S.M.A.R.T.	Health checking and alarm, Reallocation sector monitoring and alarm
SERIAL & I/O	
Serial port	1 RS-485
Sensor input	4 Dry-contacts + Sensor of IP Camera
Relay output	2 Relay
CONTROLLER	
Device	IR remote controller, Joystick Keyboard(option), Mouse
SOFTWARE	
HTML5 Webviewer	Monitoring / Event / PTZ / Playback for browser supporting HTML5
Webviewer	Monitoring / Event / PTZ / Playback for IE
Mobile viewer	Monitoring / Playback / Alarm Push / PTZ / Audio / Log View with iPhone & Android
CMS	Control Center, Max. 1024 units
SDK	HTML5 SDK, ActiveX(COM) SDK
ENVIRONMENTAL & PHYSICAL	
Dimension	378(W) x 318(D) x 51(H) mm
Weight	2.2 kg (No HDD)
Operating Temperature	5°C~45°C (41°F ~ 113°F)
Operating Humidity	80% below, free of condensation
Power	DC 12V / 5A
IPFR	Supports IPFR (Intelligent Power Failure Recovery)
Power Consumption	Typical 7.8W (w/o HDD)
Approval	KC, FCC, CE

Specifications are subject to change without notice for product improvement.

QA1.3

