m³ 400

FAST 02 2C

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where a top security technology is needed. It is equipped with two cylinders for a very convenient, reliable and redundant shooting, shoots up to 400 m³ of dense fog in 25 seconds. It is very fast and competitive.

Powerful and fast fogging system, can cover up to 400 m³ in 25 seconds.

The densest fog among all the fogging systems thanks to 80% of glycol in its fog fluid and the proprietary shooting technology.

Patented double fog cylinder is the best solution to shoot fog, tanks are easy to change and disposable. When the first cylinder is empty the machine switches automatically to the second one even during the same shot.

Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Another exclusive, patented and very useful plus that allows to detect automatically if the nozzle is tampered and sends an advise signal.

A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.

UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR FOG fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.

GENERAL SPECIFICATIONS

WEIGHT OF THE FOG MACHINE	ABOUT 15 KG
WEIGHT WITH PACKAGING	ABOUT 18 KG
UNITS ON ONE PALLET 100X120	27
DIMENSION OF THE MACHINE	30,5X23,0XH39,0
DIMENSION OF THE PACKAGING	37,0X25,0XH47,0
COLORS	WHITE
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 HOURS
HEAT UP TIME FROM COLD	ABOUT 90 MINUTES
VERTICAL OR CORNER MOUNTING	YES
HORIZONTAL MOUNTING	YES
SERIAL USB PORT FOR MONITORING	YES
NOZZLE TAMPER	YES
SERIAL BUS FOR STANDARD PROTOCOL	YES
ALARM KIT	OPTIONAL

FOG GENERATOR

NEW HEATING SYSTEM PLUS	YES
COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY)	UP TO 600 m³
COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY)	UP TO 400 m³
MAX SECONDS OF FOG EMISSION	25 sec
MAX FOG EMITTED WITH FULL FOG TANK	1500 m³
NUMBER OF CYLINDERS	2
FOG TANK CAPACITY	2 x 500 ml
SHOOTING SPECIFICATION	PROGRAMMABLE IN SECONDS
CYLINDER MODEL	VERTICAL / HORIZONTAL
CYLINDER INCLUDED	2
DOUBLE FOG TANK ADVANTAGE	YES

ELECTRICAL SPECIFICATIONS

POWER SUPPLY	230 V or 110 V
AVERAGE POWER CONSUMPTION	42 W
BATTERY PACK	YES
OPTIONAL DEMO/ANTIROBBERY KIT	YES
WIRED INPUTS ARMING AND SHOOTING	YES
WIRED OUTPUTS	YES
STANDARD COMMUNICATION PROTOCOL	YES

STANDARDS

COMPLIES WITH EUROPEAN CE	YES
FOG FLUID IS CERTIFIED	YES
MEETS EUROPEAN STANDARD	YES

PATENTED

CERTIFIED AFTER EUROPEAN STANDARDS